

SERIES FXE T - Lifting magnet Truss

Electro-permanent magnetic lifters



Picture for reference only

- ✓ Available Radio remote control with Pick Up function to lift individual plates.
- ✓ Chains and Hooks included.
- ✓ Lifting eyelet sensor -demag only when load is free
- ✓ Primary connection cable ready for 400V/ 25A fuse CEE 32A plug
- ✓ 360° LED signal tower

FXE T 2500/50			
THICKNESS of material (mm)	MAX LOAD (kg)	MAX DIMENSION (mm)	
		L (max)	B (max)
4	500	4000	1500
6	750	4000	1500
8	1250	4000	2000
10	1750	4000	2000
15	2500	4000	2500

FXE T 4000/80			
THICKNESS of material (mm)	MAX LOAD (kg)	MAX DIMENSION (mm)	
		L (max)	B (max)
4	350	4000	1500
6	700	4000	1500
8	1000	4000	2000
10	1250	4000	2000
15	2500	5000	2500
25	4000	5000	2500

FXE T 6400/80			
THICKNESS of material (mm)	MAX LOAD (kg)	MAX DIMENSION (mm)	
		L (max)	B (max)
4	500	4000	2000
6	1000	6000	2500
8	1400	6000	2500
10	2000	6000	3000
15	4000	6000	3000
25	6400	6000	3000

MODEL	MAX WEIGHT LOAD (kg)	DIMENSION (mm)			POLES nr	POLES Type	BREAK OFF kN	WEIGHT kg
		L	B	H				
FXE T2500/50	2500	1000	630	380	2x18	50	96	138
FXE T4000/80	4000	1200	500	380	2x10	80	170	175
FXE T6400/80	6400	6150	780	1900	2x16	80	272	520

Consistent sample model - many other Versions available